



AUTO MASTER

Workshop Equipment



100%



NZ OWNED
& OPERATED



PATCH RUBBER

TYRE AND TUBE

EVERYTHING FOR THE TYRE DEALER

WE PROMISE YOU A BETTER STANDARD OF SUPPORT

When we went into business over 18 years ago our aim was to raise the standards in the automotive equipment industry. Today we're just as committed. At Automaster we offer you an extensive range of high quality automotive equipment at a variety of price points. Which means you can choose reliable, hardworking products that fits your business and your budget. Less repairs and less downtime gives you more in your back pocket. And if issues arise, our experienced staff will get you up and running as quickly as possible. That's the Automaster difference.



AUTHORISED NZ DISTRIBUTORS OF:



100% Italian made - known globally as the very best tyre industry equipment available.



Top quality handpicked equipment sourced from multiple factories with the tyre changers, balancers and hoists developed by an Italian/Chinese joint venture factory.



The best lower cost hoist option available.



Premium quality car lifts 100% Manufactured in Korea.



We understand how important it is to match equipment to suit your business' individual needs. We have a full operating show room set up with most of our equipment ready to go so you can try before you buy. Available on site are different wheel and tyre combinations from 13-20" so you can compare the Chinese and Italian tyre service equipment. Also on site we have multiple hoists & wheel alignment machines set up for viewing. Just give us a call on 0800 214 604 to arrange a time.



PATCH RUBBER TYRE AND TUBE

EVERYTHING FOR THE TYRE DEALER

- Wheel Balancing Supplies
- Tyre Repair Materials & Tools
- Valves, Extensions & TPMS
- Retreading Supplies
- Air Line & Hose Reels
- Inflation Tools & Gauges
- Tyre Levers & Hammers
- Bead Breaking Tools
- Tyre & Wheel Changing Supplies, Lubricants & Equipment
- Wheels, Rims & Assemblies
- NZ's Largest Range of Inner Tubes
- Specialty Tyres for ATV, Agricultural Machines, Skidsteer, Forklift, Industrial, Lawn, Garden, Golf, Motorcycle and Trailer uses.

AUCKLAND: 0508 837 248

21 Aetna Place, Henderson, Auckland • Email: akld@patchrubber.co.nz

HAMILTON: 0508 489 737

20 Devon Road, Frankton, Hamilton • Email: ham@patchrubber.co.nz

WELLINGTON: 0800 943 777

3/65 Marsden Street, Lower Hutt, Wellington • Email: wgt@patchrubber.co.nz

CHRISTCHURCH: 0800 936 444

6 Gerald Connolly Place, Hornby Christchurch • Email: chch@patchrubber.co.nz

INVERCARGILL: 0508 472 824

11 Teviot Street, Appleby, Invercargill • Email: inv@patchrubber.co.nz



SCAN ME

PATCH RUBBER SALES REPS - IN FULLY STOCKED VANS

Dan - 021 973 138

North Auckland & Northland

Mike - 021 310 220

West & South Auckland

Jay - 021 574 450

BOP & East Auckland

Tremayne - 027 231 2021

Waikato

Brian Nant - 029 247 7876

Hawkes Bay & East Coast

Tony - 029 275 7577

Taranaki/Manawatu Area

Marty - 0220 859 061

Wellington & Wairarapa

Shannon - 021 241 4777

Upper South Island

Jordan - 029 276 1821

Christchurch

Simon - 029 276 1821

Central & Lower South Island

Steve - 027 503 3666

Invercargill & Southland



www.patchrubber.co.nz

Contents

WHEEL BALANCERS

Automaster / Corgi

Pages 4-8



TYRE CHANGERS

Automaster / Corgi

Pages 9-20



HOISTS

Peak / Automaster / Powerrex Korea / Corgi

Pages 22-46



WHEEL ALIGNERS

Corgi

Pages 47-49



WHEEL LIFTERS

Automaster / Corgi

Pages 50



BATTERY LIFT TABLE

Automaster

Page 51



PATCH RUBBER TYRE & TUBE

Tyre Repair Equipment

Page 52-53



AUTOMASTER

Contact Details

Page 52



AUTOMASTER AM-451 Wheel Balancer



SCAN ME

- Hand spin wheel balancer
- Suitable for mobile service
- Power requirement can be either 230V or 12/24V.
- AC/DC adapter supplied as standard
- Manual entry of wheel dimensions
- Dynamic, static and multiple alloy wheel modes
- Self Calibration feature
- 40mm threaded shaft
- Foot pedal holding brake
- Compact design

| SPECIFICATIONS | |
|---------------------|-------------------------|
| Max. wheel weight | 65kg |
| Wheel diameter | 33" (840mm) |
| Rim diameter | 10" - 26" (255 - 660mm) |
| Wheel width | 1.5" - 20" (39 - 510mm) |
| Balancing precision | ±1g |
| Cycle time | 7 s |
| Balancing speed | 100 -150rpm |
| Power supply | 230V or 12/24V. |
| Warranty | 1 year |
| Weight | 85kg |



AUTOMASTER AM-401F Wheel Balancer



SCAN ME

- Suited to low-med volume user looking for a low cost option
- Manual entry of wheel dimensions
- Dynamic, static and multiple alloy wheel modes
- Self Calibration feature
- 40mm threaded shaft
- Foot pedal holding brake
- Compact design
- Auto start when hood closed
- Back or front mounting
- Automatic braking after balance spin

| SPECIFICATIONS | |
|---------------------|-------------------------|
| Max. wheel weight | 75kg |
| Wheel diameter | 39" (1000mm) |
| Rim diameter | 10" - 32" (255 - 660mm) |
| Wheel width | 1.5" - 20" (39 - 510mm) |
| Balancing precision | ±1g |
| Cycle time | 7 s |
| Balancing speed | 180 rpm |
| Power supply | 230V |
| Warranty | 1 year |



AUTOMASTER PRO SERIES AM-412 Wheel Balancer



SCAN ME

- Heavy duty balancer suited to med-high volume user
- Auto entry of offset and diameter
- Dynamic, static and multiple alloy wheel modes
- Split hidden stick on weight feature
- Self Calibration feature
- 40mm threaded shaft
- Foot pedal holding brake
- Large wheel weight storage tray
- Auto start when hood closed
- Back or front mounting
- Automatic braking after balance spin



STANDARD ACCESSORIES



| SPECIFICATIONS | |
|---------------------|-------------------------|
| Max. wheel weight | 75kg |
| Wheel diameter | 39" (1000mm) |
| Rim diameter | 10" - 30" (255 - 760mm) |
| Wheel width | 1.5" - 20" (39 - 510mm) |
| Balancing precision | ±1g |
| Cycle time | 7 s |
| Balancing speed | 150 rpm |
| Power supply | 230V |
| Warranty | 2 year |

AUTOMASTER PRO SERIES AM-413E Wheel Balancer



SCAN ME

- Top Quality balancer designed for the mid – high volume shop
- FULLY automatic data entry, offset - width & diameter
- Laser line as standard, pointed at 6 o'clock position
- Automatic brake after spin
- Automatic start when wheel guard is lowered
- Four standard ALU and two ALU*balancing modes
- Split function to hide weights behind spokes of rim
- Back or front mounting
- 40mm shaft size
- Rapid optimization (OPT)



STANDARD ACCESSORIES




| SPECIFICATIONS | |
|---------------------|-------------------------|
| Max. wheel weight | 75kg |
| Wheel diameter | 39" (1000mm) |
| Rim diameter | 10" - 32" (255 - 810mm) |
| Wheel width | 1.5" - 20" (39 - 510mm) |
| Balancing precision | ±1g |
| Cycle time | 7 s |
| Balancing speed | 180 rpm |
| Power supply | 230V |
| Gross weight | 180kg |
| Warranty | 2 Year |

AUTOMASTER PRO SERIES

AM-482 Wheel Balancer



SCAN ME



- Wheel balancer with European technology
- FULL automatic data entry, offset - width & diameter
- Dynamic, 3 static modes, 5 automatically
- selected ALU modes, plus split hidden weight & OPT functions
- Automatically stops at unbalanced position ready to apply weights.
- LED lighting and laser line for weight position
- Apply weight at either 6 or 12 o'clock position.
- Large weight tray capacity

| SPECIFICATIONS | |
|---------------------|-------------------------|
| Max. wheel weight | 70kg |
| Wheel diameter | 36" (900mm) |
| Rim diameter | 10" - 26" (255 - 660mm) |
| Wheel width | 1.5" - 20" (39 - 510mm) |
| Balancing precision | ±1g |
| Cycle time | 7 s |
| Balancing speed | 150 rpm |
| Power supply | 230V |
| Gross weight | 180kg |
| Warranty | 2 Year |



AUTOMASTER CAR & TRUCK

AM-462 Wheel Balancer



SCAN ME

- The Automaster AM-462 truck wheel balancer is one of the best value large truck & bus tyre computer wheel balancers available.
- One balancer that can balance passenger steel or alloy wheels and truck & bus wheels.
- Self calibration feature
- Ounce/gram selectable & mm/inch selectable
- Normal, static, AL1, AL2, balance modes
- Multiple cones and spacer plates
- Back or front mounting
- Pneumatic wheel lift included

| | |
|---------------------|------------------------------|
| Max. wheel weight | 200kg |
| Wheel diameter | 1200mm |
| Rim diameter | 10" - 32" (255 - 810mm) |
| Wheel width | 1.5" - 20" (39 - 510mm) |
| Balancing precision | ±1g for Car / ±10g for Truck |
| Cycle time | 7s for Car / 15s for Truck |
| Balancing speed | 150 rpm Car / 90rpm Truck |
| Power supply | 230V |
| Air Supply | 8-10 bar |
| Warranty | 1 Year |



CORGI EM9250 Compact Wheel Balancer



- **Two versions available**
- **PREMIUM:** version with automatic input of wheel diameter and distance, & Electrical clamping brake
- **PREMIUM FULL KIT:** Version with full auto data entry, Width sonar, LED, lazerline & Electrical clamping brake
- Compact design suited for medium volume requirements
- Automatic wheel positioning at end of spin
- Static, dynamic and 7 auto selected ALU programs
- Programs - OPT, hidden & split weight
- Made in Italy

| SPECIFICATIONS | |
|---------------------------------|--------------|
| Wheel diameter - manual setting | 1-32" |
| Wheel diameter - auto setting | 11-28" |
| Balancing speed | 90 - 130 RPM |
| Rim width | 1.5 - 20" |
| Max tyre diameter (with guard) | 1117mm / 44" |
| Average cycle time | 7 sec |
| Power supply | 230V |
| Max wheel weight | 75kg |
| Warranty | 2 Years |



STICK ON WEIGHT DISPENSER



LASERLINE FOR STICK ON WEIGHT



AUTOMATIC WIDTH SENSOR



LED LIGHT ILLUMINATES THE WORK AREA

This product has been accredited by:



CORGI EM9550 LASERLINE PLUS Wheel Balancer



- Fully featured suited for the most demanding environments
- Full automatic data entry for offset, width & diameter
- Laser line & LED for application of stick on weight
- Automatic wheel positioning & locking at end of spin
- Space saving hood - allows positioning against wall
- Programs - multi operator - OPT, hidden & split weight
- Extra large weight tray
- 40 mm threaded shaft
- FSP - Fast Selection Balancing Program
- EM-9550C - with auto electromechanical clamping
- Made in Italy

| SPECIFICATIONS | |
|---------------------------------|---------------|
| Wheel diameter - manual setting | 1-32" |
| Wheel diameter - auto setting | 11-28" |
| Balancing speed | 75-85- 95 RPM |
| Rim width | 1.5 - 20" |
| Max tyre diameter (with guard) | 1117mm / 44" |
| Average cycle time | 5.5 sec |
| Power supply | 230V |
| Max wheel weight | 75kg |
| Warranty | 2 Years |



STICK ON WEIGHT DISPENSER



OPTION EM9550C = AUTO LOCKING WHEEL CLAMP SYSTEM



LASERLINE FOR STICK ON WEIGHT



AUTOMATIC WIDTH SENSOR



LED LIGHT ILLUMINATES THE WORK AREA

This product has been accredited by:



CORGHI EM9580C LASERLINE
Touchscreen Wheel Balancer

- Wheel balancer with touch screen monitor, electronic clamping and automatic wheel size detector.
- Simple select Touchscreen interface
- Full automatic data entry for offset, width & diameter
- SmartArm Auto select & LaserBlade position guide
- Laser line & LED for application of stick on weight
- Automatic wheel positioning & locking at end of spin
- Space saving hood - allows positioning against wall
- **Weight saving management program** - including LESS WEIGHT, which cuts Job times (20%) and reduces the quantity of counterweights used (30%), for more cost-effective, environmentally friendly operation.

100%
MADE IN ITALY



STICK ON WEIGHT DISPENSER




AUTO LOCKING WHEEL CLAMP SYSTEM



LASERLINE FOR STICK ON WEIGHT



LED LIGHT ILLUMINATES THE WORK AREA



AUTOMATIC WIDTH SENSOR

| SPECIFICATIONS | |
|---------------------------------|------------------|
| Wheel diameter - manual setting | 1-35" |
| Wheel diameter - auto setting | 10-28" |
| Balancing speed | 75 - 85 - 98 RPM |
| Rim width | 1.5 - 20" |
| Max tyre diameter (with guard) | 1117mm / 44" |
| Average cycle time | 5.5 Sec |
| Power supply | 230V |
| Max wheel weight | 75kg |
| Warranty | 2 Years |

CORGHI EM9780C PLUS
Wheel Balancer - TouchlessLine

- Featuring the latest technology for demanding environments
- Full automatic operation - no manual inputs required
- Laser Pointer & LED for application of stick on weight
- 22" Touchscreen Interface selection
- Automatic clamping
- Automatic wheel positioning & locking at end of spin
- Space saving hood - allows positioning against wall
- Programs - multi operator - OPT, hidden & split weight
- **Weight management programs including LESS WEIGHT**, which cuts job times (20%) and reduces the quantity of counterweights used (30%), for more cost effective, environmentally friendly operation
- Automatic hidden weight program
- Optional run out diagnostic sonar
- FSP - Fast Selection Balancing Program

100%
MADE IN ITALY



STANDARD ACCESSORIES



LASER POINTER FOR STICK ON WEIGHT



AUTOMATIC WIDTH SENSOR



STICK ON WEIGHT DISPENSER

| SPECIFICATIONS | |
|---------------------------------|------------------|
| Wheel diameter - manual setting | 2-35" |
| Wheel diameter - auto setting | 10-32" |
| Balancing speed | 75 - 85 - 98 RPM |
| Rim width | 1.6 - 23.6" |
| Max tyre diameter (with guard) | 1117mm / 44" |
| Machine weight | 183 kg |
| Power supply | 230V |
| Max wheel weight | 75kg |
| Warranty | 2 Years |

This product has been accredited by:



AUTOMASTER AM-106B Tyre Changer



- The Automaster AM-106B swing arm tyre changer is the perfect changer for a small workshops or an ATV/motorcycle dealer.
- Side swinging head for space saving operation
- Rust free stainless steel bead breaking cylinder
- Quality water trap and oiler
- Single speed turntable rotates in both directions
- Includes tyre inflation gauge, lube brush, tyre lube and heavy duty tyre lever
- Includes plastic jaw protectors, head inserts and clip on rim proctor




| SPECIFICATIONS | |
|-----------------------------|--|
| Rim clamping | 10" - 22" External 12" - 24" Internal |
| Max wheel diameter | 1000 mm (39") |
| Max wheel width | 340 mm (13") |
| Bead-breaker cylinder force | 3000 kg |
| Max operating pressure | 10 bar (140 psi) |
| Power supply | 230V |
| Warranty | 1 Year |

AUTOMASTER AM-202IT Tyre Changer



- The Automaster AM-202IT tyre changer has a pneumatically controlled tilt back post and is the perfect changer for workshops that do tyres or an ATV/ motorcycle dealer
- Suitable for alloy & steel wheels
- Rust free stainless steel bead breaking cylinder
- Pneumatic tilting post
- Quality water trap and oiler
- Extra heavy duty shafts to avoid distortion
- Pneumatic locking mechanism automatically gives vertical and horizontal clearance from the rim
- Includes lube brush, tyre lube & HD tyre lever
- Tubeless air blast inflation system



| SPECIFICATIONS | |
|-----------------------------|--|
| Rim clamping | 10" - 22" External 12" - 24" Internal |
| Max wheel diameter | 1000 mm (39") |
| Max wheel width | 340 mm (13") |
| Bead-breaker cylinder force | 3000 kg |
| Max operating pressure | 10 bar (140 psi) |
| Power supply | 230V/380V |
| Warranty | 1 Year |

AUTOMASTER PRO SERIES AM-203IT Tyre Changer



- The Automaster AM-203IT Pro Series Heavy duty tyre changer is our most popular in the Automaster line up.
- It has a pneumatically controlled tilt back post and is the perfect changer for busy workshops or tyre shops.
- Designed to change the tyres on both high priced alloy wheels and steel wheels without damaging the rim or the tyre
- Tubeless air blast inflation system - pedal controlled
- Extra heavy duty shafts to avoid distortion under load
- Anti wear roller to eliminate play in top shaft
- Powerful bead breaker designed to break even the most stubborn and rusted beads without damage.
- Pneumatic locking mechanism
- Automaster Tyre machines deliver years of dependability because they are built using only the highest quality component parts.



OPTIONAL SINGLE OR TWIN HELPER ARMS



STANDARD ACCESSORIES



3ph = 2 SPEED MOTOR
1ph = SINGLE SPEED MOTOR

| SPECIFICATIONS | |
|-----------------------------|--|
| Rim clamping | 10" - 22" External 12" - 24" Internal |
| Max wheel diameter | 1000 mm (39") |
| Max wheel width | 350 mm (14") |
| Bead-breaker cylinder force | 3000 kg |
| Max operating pressure | 10 bar (140 psi) |
| Power supply | 230V/380V |
| Max spindle torque | 1200 Nm |
| Warranty | 2 years |

AUTOMASTER PRO SERIES AM-204IT Tyre Changer



- The Automaster AM-204IT Pro Series tyre changer is the perfect machine for shops needing to do a range of extra large 4x4 or performance wheels
- Heavy duty machine designed for the mid - high volume shops
- Tubeless air blast inflation system - pedal controlled
- Rust free stainless steel bead breaking cylinder
- Extra large and wide opening bead breaker is designed to break even the most stubborn and rusted beads without damage.
- Quality water trap and oiler
- Extra heavy duty shafts to avoid distortion under load
- Anti wear roller to eliminate play in top shaft
- Pneumatic locking mechanism automatically gives clearance from the rim
- Available with none, one or twin helper arms



WITH OPTIONAL HP1 HELP ARM



OPTIONAL TWIN HELP ARMS



STANDARD ACCESSORIES



3ph = 2 SPEED MOTOR
1ph = SINGLE SPEED MOTOR

WITH OPTIONAL LEFT & RIGHT HELPER ARMS

| SPECIFICATIONS | |
|-----------------------------|--|
| Rim clamping | 12" - 28" External 14" - 30" Internal |
| Max wheel diameter | 1200 mm (47") |
| Wheel width | 3" - 17" (450mm) |
| Bead-breaker cylinder force | 3000 kg |
| Max operating pressure | 10 bar (140 psi) |
| Power supply | 230V/380V |
| Gross weight | 310 kg |
| Warranty | 2 Year |

AUTOMASTER AM-303LA Commercial Tyre Changer



SCAN ME

- Automaster AM-303LA multi-functional universal commercial truck & tractor tyre changer with an automatic tilting/shifting tool holder arm.
- Suitable for any truck and heavy-duty wheel from 14"-47 inch rim, diameter 2300mm and width 1100mm.
- Two speed hydraulic chuck, with 5 different rim locking points
- The AM-303LA handles off-road tyres, agricultural tyres, super singles, tractor and skidder tyres and is the perfect choice for the truck tyre centre that does a wide variety of tyres.



| SPECIFICATIONS | |
|----------------------|-------------------------------|
| Max wheel width | 1100mm / 43" |
| Max wheel diameter | 2300mm/91" |
| Max wheel weight | 1500kg |
| Bead breaker force | 2700kg |
| Clamping capacity | 14 - 46" or 56" with adapters |
| 2-speed gear motor | 2.6kW/3.2kW, 5-10 rpm |
| Hydraulic Pump Motor | 1.1kw 380V-3Ph |
| Warranty | 2 years |

AUTOMASTER AM-356 Super Heavy Duty Tyre Changer



SCAN ME

- Multi-functional universal Automatic HD tyre changer
- Designed and engineered to handle rim sizes from 14"-47" (56" with optional kit) inches and tyre diameters in excess of over 2600mm.
- Two speed hydraulic chuck, with 5 different rim locking points
- Automatic tilting/shifting tool holder arm
- Automatic rotation of the tool head
- The AM-356 has all the power you will need with twin motors,
Hydraulic Pump Motor 4.0kw 380V-3Ph
Gearbox Motor 2.6/3.2kw 380V-3Ph 2 speed



The AM-356 handles off-road tyres, agricultural tyres, super singles, tractor, skidder and earth mover tyres and is the perfect choice for the commercial tyre centre that does a wide variety of tyres.

| SPECIFICATIONS | |
|--------------------|------------------------------|
| Max wheel width | 1500mm |
| Max wheel diameter | 2600mm |
| Max wheel weight | 1700kg |
| Bead breaker force | 3500kg |
| Clamping capacity | 14 - 47" (56" with adapters) |
| Power supply | 400v 3ph |
| Machine weight | 1600kg |
| Warranty | 2 years |



OPTIONAL ACCESSORIES FOR AUTOMASTER EQUIPMENT



Balancer Kit



Balancer Motorcycle Kit



LT Truck Cone & Spacer Kit



Deluxe Motorcycle Adapters



Motorcycle & ATV Adapters



Lifting Blocks



**Bead Pressing Roller
(AM-106B Machine)**



**Quick Change Adapter +
Plastic Mounting Head**



Wheel Lifter



**Motorcycle
Mounting Head**



CELEBRATING 60 YEARS OF BRILLIANCE

Corghi has retained an international unparalleled reputation for quality and performance for more than 60 years, and this reputation remains just as strong today, with the Corghi group being the world's largest producer of wheel servicing equipment.

In 1947, the brothers Erminio and Remo Corghi started their business with the main objective: Total quality! This mental and professional attitude still permeates today in all aspects of the Corghi work environments.

With the automobile boom in 1960 the Corghi brothers invent and patent the world's first tyre changer. Their company takes off and never stops soaring. With continuous research, development and diversification Corghi is still the absolute global leader in the tyre service equipment sector.

Together with its partners, Corghi has the world's largest, most complete automotive equipment distribution network, covering almost 150 countries, with subsidiaries in Spain, France, Germany, United States, China, Australia and Brazil.

Corghi is especially proud to be the sole supplier of equipment to Ferrari workshops - including the Formula 1 Team - providing its entire range of products.

STILL 100% MADE IN ITALY

The traditional Corghi range is still 100% made in Italy, and history has proven Corghi products to have supreme performance and endurance in the most demanding work environments.



CORGI EM9050 Space Saver Wheel Balancer



SCAN ME

- Designed to offer great performance in confined spaces
- It is the smallest in the range but boasts advanced programmes featured in higher level models
- Lever-actuated motorised spin or manual spin version
- SmartArm automatic wheel size detection-Automatic acquisition of distance, diameter and width with integrated FSP (Fast Selection Program) function that automatically activates the balancing programmes avoiding the use of the keyboard
- Lever operated clamping brake.
- Multi-Functional digital display allows for immediate and intuitive access to all the programmes and functions
- Next gen measuring unit derived from higher level models.
- Three systems for positioning adhesive counterweights: weight holder clips or manually at 6 o'clock or at 12 o'clock
- 100% made in Italy

| SPECIFICATIONS | |
|---------------------------|-------------------------|
| Balancing speed | 98 rpm |
| Average spin time | 5 Sec |
| Settable rim width values | 1.5-20" |
| Settable wheel diameter | 1"-35" Man /10"-28"Auto |
| Maximum wheel weight | 85kg |
| Machine weight | 67kg |
| Supply voltage | 24VDC or 230V - 1Ph |
| Warranty | 2 Years |

Optional 12V power supply kit (only for Hand Spin version)

Manual Spin version

Motor Spin version



VERSIONI MOTORIZZATE
MOTORIZED VERSIONS

VERSIONI A LANCIO MANUALE HS
HS MANUAL SPIN VERSIONS

CORGI Artiglio Space Saver Tyre Changer



SCAN ME

- Artiglio Space Saver is an automatic tyre changer featuring a pneumatic controlled side rotating post for space saving
- Saving almost 1m its suitable for places with little space and/or mobile service vans
- A robust and reliable tyre changer for intensive use
- Includes pneumatic bead depressor help arm
- Includes plastic jaw protectors and mounting head inserts
- Includes lube, lube brush, container & HD tyre lever
- Optional ATV or M/C adapters
- 100% made in Italy

| SPECIFICATIONS | |
|-----------------------------|--|
| Rim clamping | 10" - 24" External 13" - 26" Internal |
| Max tyre diameter | 1035 mm (40") |
| Max tyre width | 350 mm (14") |
| Bead breaker cylinder force | 2500kg |
| Max operating pressure | 10 bar (140 psi) |
| Power supply | 230V 1PH 1 Speed |
| Max spindle torque | 1200 Nm |
| Warranty | 2 years |



The demounting and mounting tool is a major innovation for this tyre changer. The addition of the newly-designed guide tab offers significant support during mounting step, facilitates tyre installation on the rim and avoids possible damage to the tyre. Plastic protections are also present to avoid scratching the rims. Very effective also on RFT, UHP, BSR tyres in combination with the bead pressing tool



CORGI A224TI Tyre Changer



SCAN ME

- Economic high spec machine for mid - high demand shops
- TI tubeless air blast system
- Attached pedal controlled inflation gauge
- Quality stainless steel bead breaking cylinder
- Pneumatic tilting column
- Extra heavy duty shafts to avoid distortion under load
- Simultaneous pneumatic locking of the horizontal & vertical arm
- Includes plastic jaw protectors and mounting head inserts
- Includes lube, lube brush, container & HD tyre lever
- Optional ATV or M/C adapters
- 100% made in Italy

| SPECIFICATIONS | |
|-----------------------------|--|
| Rim clamping | 10" - 24" External 13" - 26" Internal |
| Max tyre diameter | 1100 mm (43") |
| Max tyre width | 350 mm (14") |
| Bead breaker cylinder force | 2500kg |
| Max operating pressure | 10 bar (140 psi) |
| Power supply | 380v/3ph or 230V 1PH |
| Max spindle torque | 1200 Nm |
| Warranty | 2 years |



OPTIONAL ACCESSORIES
SP300 HELPER



OPTIONAL ACCESSORIES
SP2300 HELPER



STANDARD
ACCESSORIES



CORGI A2025TI Tyre Changer



SCAN ME

- High spec premium machine for mid - high demand shops
- Pedal controlled inflation gauge & TI tubeless air blast system
- Variable torque mini inverter single phase motor give complete control with the most difficult tyres
- Adjustable bead breaking pad unit features a dual-position telescopic support (CORGI patent) & the length of bead breaker arm can also be extended
- Automatic movement of vertical shaft by air spring & simultaneous pneumatic locking of horizontal and vertical shafts plus automatic head positioning in the ideal working position
- Optional ATV or M/C adapters

| SPECIFICATIONS | |
|-----------------------------|--|
| Rim clamping | 10" - 24" External 13" - 26" Internal |
| Max tyre diameter | 1100 mm (43") |
| Max tyre width | 360 mm (14") |
| Bead breaker cylinder force | 2500kg |
| Max operating pressure | 10 bar (140 psi) |
| Power supply | 230V DV MI - 2 Speed |
| Max spindle torque | 1300 Nm |



OPTIONAL ACCESSORIES
SP2300 HELPER



OPTIONAL ACCESSORIES
SP300 HELPER



STANDARD
ACCESSORIES

NEW ZEALAND'S
MOST POPULAR
TYRE MACHINE



This product has been accredited by:



CORGHI ARTIGLIO MASTER JOLLY Tyre Changer



- **AUTOMATIC" VERSION WITH PNEUMATIC WHEEL CLAMPING ALSO AVAILABLE**
- Full touchless lever-less tyre changer
- Attached pedal controlled inflation gauge
- Wheel lifter
- Bead depressor with adjustable working height
- Dual bead breaker discs
- MOTOR INVERTER DRIVE SYSTEM - the right torque at the right speed (7 - 18 RPM)
- Conventional, low profile and run flat tyres
- System demounting movement able to reduce the tension on the tyre without ever touching the rim
- Automatic location of the tyre bead, with no contact with the rim itself, regardless of its shape
- Made in Italy



| SPECIFICATIONS | |
|-------------------|------------|
| Rim diameter | 12-26" |
| Max tyre width | 14" |
| Max tyre diameter | 1100mm |
| Rotation speed | 7-18 rpm |
| Machine weight | 400kg |
| Power supply | 230V DV MI |
| Warranty | 2 years |

"Touchless Leva la leva" the only existing solution that:

NEVER TOUCHES THE RIM, during any working phase and annuls all tension on the tyre during the tyre demounting/mounting phases. Ergonomic and multi-functional consoles that makes it possible to electronically set the rim diameter and obtain the positioning of the work tools in a quick,practical and safe manner.



STANDARD ACCESSORIES



This product has been accredited by:



CORGI ARTIGLIO MASTER 28 Tyre Changer



SCAN ME



The perfect synthesis

In 2001 Corgi revolutionised the world of tyre changers by introducing the concept of leverless work. Since then, they have continued to develop this technology that today, despite countless attempts to copy it, still remains unmatched thanks to the "SMART Corgi System" characteristics, The only existing technology on the market that allows you to:

- NEVER TOUCH THE RIM, during any of the work phases;
- Cancels any tension on the tyre during the demounting/ mounting phases.

This is the Corgi difference

This technology is at the heart of the new Artiglio Master 28 and it is the perfect synthesis of the experiences gained over these 18 years.

Electronic setting of the rim diameter with auto positioning of all working tools.

The new demounting tool head is a perfect combination of that found on the Artiglio Master 26 and that on the Artiglio Master CODE,merging the advantages of the two solutions.

MOTOR INVERTER DRIVE SYSTEM - the right torque at the right speed (7 - 18 RPM)

| SPECIFICATIONS | |
|-----------------------------|--------------------|
| Rim diameter | from 13" to 28" |
| Max tyre diameter | 1100 mm |
| Power supply | 230V 1PH 20 Amp |
| Max tyre width | 16" - 406 mm |
| Rotation torque | 1100 Nm |
| Rotation speed | 7-18 rpm |
| Maximum bead breaking range | 18" |
| Bead breaker stroke | 450 mm |
| Bead breaker force | 7600 N |




This product has been accredited by:




**CORGHI HD500 Plus
Truck & Bus Tyre Changer**



- New, compact, fast & easy to use
- Turntable increased rpm, from 7.5 to 9 rpm
- New rim clamping jaws
- New reinforced frame
- New Control Console with accessory support
- Control console adjustable in height
- New gearbox unit
- The 2 hydraulic-powered trolleys, the chuck holder and the tool carriage, allow the wheel to be moved rapidly.
- This always puts it in the best position to be demounted and mounted.
- Multi-purpose turntable covers 14-26"
- Designed to take up the least amount of space



| SPECIFICATIONS | |
|--------------------|--------------------|
| Max wheel width | 695mm / 30" |
| Max wheel diameter | 1400mm |
| Max wheel weight | 700kg |
| Bead breaker force | 14000n |
| Clamping capacity | 14 - 26" |
| Power supply | 400v 3ph (1ph opt) |
| Machine weight | 500kg |
| Warranty | 2 years |




Hydraulic control unit motor 0.75 Kw (3ph)
Turntable motor 1.1 Kw (3ph)

**CORGHI HD850A
Truck & Bus Tyre Changer**



- Automatic tyre changer for use on truck and bus wheels of any type - with tube or tubeless - up to 26" diameter.
- New re-engineered structure, new power unit and new hydraulic cylinders - these are the main component improvements of the new HD 850 A.
- The New structure has been designed to guarantee resistance and robustness.
- Hydraulic tool-holder arm with automatic raising and rotation of the tool and disc.
- Synchronized and opposite movement of the tool-holder and clamp arm structure is simultaneous.

| SPECIFICATIONS | |
|--------------------|----------|
| Max wheel width | 780mm |
| Max wheel diameter | 1500mm |
| Max wheel weight | 700kg |
| Bead breaker force | 20000N |
| Clamping capacity | 14 - 26" |
| Power supply | 400v 3ph |
| Machine weight | 620kg |
| Warranty | 2 years |



Compact Dimensions of less than 2 metres



CORGI HD1400 Evolution Auto Heavy Duty Tyre Changer

Truck, Bus, Agricultural, Loader & Skidder



- Fully automatic universal tyre changer
- Robust performance, reliability, and safety
- The world's first tyre changer with a hydraulic motor for operating the turntable's gear motor
- Maximum torque at any of the three speeds
- Optional - latest radio communication technology with 2.4 GHz wireless remote accessory
- Synchronized and opposite movement of the tool-holder and clamp arm structure is simultaneous in order to ensure faster operating speeds
- Features ultra-slow speed setting for difficult tyres



| SPECIFICATIONS | |
|--------------------|----------|
| Max wheel width | 1470mm |
| Max wheel diameter | 2500mm |
| Max wheel weight | 1900kg |
| Bead breaker force | 30000n |
| Clamping capacity | 14 - 58" |
| Power supply | 400v 3ph |
| Machine weight | 1160kg |
| Warranty | 2 years |



CORGI HD1800 Hydrus Super Sized Extra Heavy Duty Tyre Changer


Corghi can now offer you the future of oversize tyre changers! Everything about this tyre changer says power and Corghi takes innovation one step further! The HD1800 Hydrus will always be by your side with its unfailing force. Forget the risks of demounting the wheels of agricultural, earth movement or deforestation vehicles - now the job is far more simple, and it's much easier to complete it without any effort. At the same time, you have an innovative, easy way to demount truck wheels, even with such a powerful tyre changer.



- The HD1800 Hydrus is a combination of robustness and simplicity
- Fully automatic universal tyre changer
- Robust performance, reliability, and safety
- Hydraulic gear motor with 3 speeds 4 - 6 - 10 rpm
- Maximum torque at any of the three speeds



| SPECIFICATIONS | |
|----------------------------|-------------------|
| Max wheel width | 1800mm |
| Max wheel diameter | 3000mm |
| Max wheel weight | 3000kg |
| Bead breaker force | 4588kg |
| Clamping capacity | 14 - 60" |
| Hydraulic power unit motor | 400v 3ph - 4,8 kW |
| Machine weight | 1980kg |
| Warranty | 2 years |



OPTIONAL ACCESSORIES FOR CORGHI EQUIPMENT



Truck Changers Accessories & Rim Clamps



Plastic Mounting Head



8"-24" ATV Adapters




15"-23" Motorcycle Adapters



Plastic Protectors



**TT-0 Wheel Lifter
for Wheel Balancers**



Wheel Balancing Accessories


AUTOMASTER SERVICE GUARANTEE
OUR VICE-GRIP GUARANTEE
 If you're not happy, we replace or refund in full.

We work to ensure that we can provide a range of quality products at a variety of price points. Our aim: to provide the very best price/performance ratio with the lowest overall ownership costs.

Fewer repairs, less downtime all adding up to more money in our clients' back pocket. And if advice or service is needed, we back our products with in-depth technical knowledge and a can-do 'customer comes first' attitude.

Simply put, we're here to make your business perform at it's peak and if you're not happy we're not happy.

Over the last 18 years we've learned that not every customer has the exact same set of requirements. In other words there is no one-size-fits-all solution. By understanding the likely lifetime requirement of your equipment – we can help you to find the best value product, not just in terms of upfront price, but also as an ongoing cost to your business.



PEAK P-209X
Two Post Base Plate Hoist




- Revolutionary double lock system installed in both columns.
- Automatically activated double safety locks built into each column, released by one release lever make the Peak 209X floor plate lift one of the safest and easiest to operate floor plate lift in the industry.
- Single-point safety release allows the technician to easily release both column locks from one side
- Manufactured to ANSI standard & European CE Safety Certified
- 3/8" aircraft quality cables used for synchronization
- Self-lubricating UHMW Polyethylene sliders and bronze bushings
- Only needs 100mm of concrete and single phase power supply
- Stackable screw up rubber pad with 2.5" extension adapters
- Low cost commercial grade lift

| SPECIFICATIONS | |
|-----------------------|-----------------------------|
| Capacity | 4000kg |
| Max height | 1940-2210mm |
| Min height | 90mm |
| Lifting time (approx) | 49sec |
| Weight | 675kg |
| Power supply | 230V 1PH 15Amp |
| Warranty | 2 Year Full 5 Year Steel |



Only needs a minimum of 100mm of concrete for installation



Single-point safety release
The single-point safety release makes it easy for the operator to unlock both columns locks from one column, and more reliable.



4 three-stage arms are suitable for more vehicles.



Two Locks, One Release, Only Available By PEAK.






Automatic arm restraints



Self-lubricating bronze bush, no need frequently change.



Screw up feet & 2.5" 4x4 extensions









PEAK P-209C

Two Post Clear Floor Hoist



- Low cost commercial grade hoist
- Single-point safety release allows the technician to easily release both column locks from one side
- Dual hydraulic full length cylinders
- Manufactured to ANSI standard & European CE Safety Certified
- Only needs 100mm of concrete and single phase power supply
- 3/8" aircraft quality cables used for synchronization
- Self-lubricating UHMW polyethylene sliders and bronze bushings
- Two height settings – low or high setting to suit different roof heights
- Screw up feet with 2.5" Stackable extension adapters
- Overhead safety shut-off device prevents vehicle damage
- 4 three-stages arms are suitable for a wider range of vehicles

| SPECIFICATIONS | |
|-----------------------|-------------------------------|
| Capacity | 4000kg |
| Max height | 1815-2085mm |
| Min height | 90mm |
| Lifting time (approx) | 52sec |
| Weight | 640kg |
| Power supply | 230V 1PH 15Amp |
| Warranty | 2 Years Full 5 Years Steel |




Automaster Equipment formed in 2005 with a clear mission to offer a comprehensive range of quality automotive workshop equipment and back it up with the best after-sales service. Today, our commitment remains the same as always – setting the standard in the auto equipment industry.

Thanks to our hands on buying approach, we have intimate knowledge of the equipment we import. We regularly visit every factory and if we don't think the product is good enough we ask them to make it better.

Specifying only the very best quality components like balance cables, oil pumps, cylinders & electric motors (plus all other components) Automaster products will provide reliable, durable performance even in the most demanding environments.

Automaster Equipment keeps in stock a complete inventory of spare parts for the equipment we sell, and employs a specialist parts manager.

We know that some businesses will always want the highest quality. Some want quality solutions, but at a reasonable price. While others will simply want the lowest priced equipment on offer. So when we meet our customers, we listen very carefully and get an in-depth understanding of their business. From here we find a solution that meets their technical requirements, their capital budget and how they want to manage their ongoing ownership costs.






AUTOMASTER AM-7251 Single Post Lift



- Fully mobile single post lift (unloaded)
- For fast and safe lifting of vehicles
- Mechanical safety locking system
- Four extendable swivel lifting arms
- Double screw adjustable lift pads
- Lift pad adapter kit included (for vans / 4x4)
- Single phase power supply

| SPECIFICATIONS | |
|-----------------------|----------------|
| Capacity | 2500kg |
| Max height | 1755-1835mm |
| Min height | 115mm |
| Lifting time (approx) | 45sec |
| Weight | 860kg |
| Power supply | 230V 1PH 15Amp |
| Warranty | 2 Years |



**FREE 4x4
Adapters**





AUTOMASTER AM-7251DC
Mobile Single Post Car Hoist -
24V DC Battery Operated



- This machine is operated by a powerful 24v DC Battery pack, which gives it the advantage of having no trailing wires during operation
- Built in 240v - 24v D.C. charger
- Single-point safety release
- Automatic arm restraints
- Fully Mobile (When unloaded)
- Four Extendable Swivel Lifting Arms
- Double Screw Adjustable Lift Pads
- 12 piece Lift Pad Adaptor Kit Included (For vans / 4x4) 1.5", 3" & 6" extension adapters
- European CE safety certified

| SPECIFICATIONS | |
|----------------------------------|-------------|
| Capacity | 2500kg |
| Max height | 1755-1835mm |
| Min height | 115mm |
| Lifting time (approx) | 45sec |
| Weight | 860kg |
| Power supply for battery charger | 230V 1ph |
| Warranty | 2 Year |



AUTOMASTER AM-6140E



Two Post Base Hoist




SCAN ME

- Open top design is perfect for servicing of high roof vehicles and vans with roof mounted ladder racks.
- This lift is also a great option for workshops with low roof height that can not fit a clearfloor lift.
- Suitable for 4 x 4's, vans , low cars, American cars, utes etc.
- Easy to operate control panel with Up, Lock & Down buttons.
- Locking system automatically engages & unlocks when down button pressed
- Double screw up feet with 80mm 4x4 height extensions
- Lifting height limit switches prevents over extension of hydraulic cylinders
- Asymmetric arm configuration and extra wide design for easy door opening
- Dual cylinder lifting system with balance cables
- European CE Safety Certified
- Optional base plate extensions for concrete between 100-150mm

| SPECIFICATIONS | |
|-----------------------|-------------|
| Capacity | 4000kg |
| Max height | 1900mm |
| Min height | 98mm |
| Lifting time (approx) | 40sec |
| Weight | 700kg |
| Power supply | 230V / 380V |
| Warranty | 3 Year |



FREE 80mm Long 4x4 Adapters



AUTOMASTER AM-6246R Two Post Hoist 4.5T




SCAN ME

- Symmetrical or asymmetrical installation
- 3 stage front 2 stage rear arms
- Full length hydraulic cylinders with Italian seals
- Top quality motor & pump unit
- Remote control for up and lock
- Suitable for 4 x 4's, vans, low cars, American cars, utes etc.
- Dual cylinder lifting system with balance cables
- Tool trays attached to each arm
- Safety shutoff bar across top of hoist
- Ultra low arm design with 80mm 4x4 extensions supplied
- Rubber door protection pads
- Low service costs
- High motor position
- Can be installed in narrow or wide configuration and with the motor high up on the front of the column, it is completely out of the way.
- There is also a high and a low setting for the top cross bar depending on available roof height.
- **Only needs a minimum of 100mm of concrete for installation**




| SPECIFICATIONS | |
|-----------------------|---|
| Capacity | 4500kg |
| Max height | Std -1794-1950mm |
| Min height | 88mm |
| Lifting time (approx) | Single phase 52sec Three phase 42sec |
| Weight | 730kg |
| Power supply | 230V or 380V |
| Warranty | 3Year |

Symmetrical installation



Asymmetrical installation



AUTOMASTER AM-6255R Two Post Hoist 5.5T





SCAN ME

- Massive lifting capacity of 5500Kg
- Three options for total height 5200mm 5320mm 5420mm
- 4 x three stage telescoping arms with arm extensions
- With arm extensions fitted maximum arm length 1950mm
- Double screw up feet with 80mm & 180mm foot height extensions.
- Single point electrical safety lock release system
- Column design incorporates special Double S bends to increase column strength.
- High motor position & top quality motor & pump unit
- Dual cylinder lifting system with balance cables
- Safety shutoff bar across top of hoist
- Rubber door protection pads.
- Minimum of 150mm of concrete for installation



| SPECIFICATIONS | |
|-----------------------|-------------|
| Capacity | 5500kg |
| Lifting height | 1950mm |
| Min height | 106mm |
| Lifting time (approx) | 55sec |
| Weight | 700kg |
| Power supply | 230V / 380V |
| Warranty | 3 Year |




POWERREX KOREA SL2950H
Two Post Hoist




- Premium quality, feature rich, genuine 100% Korean manufactured lifts
- 3 stage front 2 stage rear arms, ultra low arm design with 80mm 4 x 4 adapters
- Automatically activating electrical locking lift with a four button control box featuring Up, Lock, Lower & Direct Down buttons plus remote control.
- High 3850mm and a low 3600mm setting for the top cross bar depending on available roof height in your workshop
- Safety shutoff bar across top of hoist
- Rubber door protection pads
- Meets Australia/NZ safety regulations
- Optional top bar 1Mtr height extension kit
- Optional base plate extensions for concrete between 100-150mm

| SPECIFICATIONS | |
|-----------------------------|--------------|
| Capacity | 4500kg |
| Max height | 1920-1975mm |
| Min height | 93mm |
| Lifting time (approx) - 3PH | 30-40sec |
| Weight | 700kg |
| Power supply | 230V or 380V |
| Warranty | 3 Years |



Not including 4x4 adapters





CORGI HC4502


Two Post Hoist



- Industry leading 1980mm lifting height
- Options of installation in symmetrical or asymmetric version.
- 3000-3200mm clearance inbetween posts (Width is adjustable)
- Standard height of two-post connection: 4,050 mm
- Solid 1pce post with 8 fold bending structure & internal reinforcement
- Safety over height shut off bar
- 4 three-stage symmetric arms made with 8mm thick steel - at full extension the arms provide 1750mm of reach
- Tool trays on each arm & Rubber door protections on each carriage
- 80mm & 180mm 4x4 extensions included
- Base plate is 20mm thick & secured to the floor by 8 true bolts
- Electro magnet safety release 24V
- Extra long 1800mm long carriage for stability and load distribution
- Optional 600mm or 1200 mm column extension kit




| SPECIFICATIONS | |
|-----------------------------|-------------|
| Capacity | 4500kg |
| Max height | 1980-2160mm |
| Min height | 100mm |
| Lifting time (approx) - 3PH | 45sec |
| Weight | 1150kg |
| Power supply | 380V |
| Warranty | 3 Years |




8 fold bending structure & internally built in reinforcement

1.2 LAYOUT SYMMETRIC WAY TO INSTALLATION



1.21 LAYOUT ASYMMETRIC WAY TO INSTALLATION



**AUTOMASTER AM-9685 8500kg
Wireless Mobile Column lift**



- 8.5-tonne capacity per column, 2 to 12 columns can be linked together with wireless communication
- Suitable for lifting trucks, buses, forklifts, utes & 4x4's etc..
- Each heavy duty mobile column is powered by a DC motor equipped with a set of rechargeable batteries & wireless communication.
- Columns can also be connected with cables for wired communication.
- The hydraulic pallet jack system on each column allows for unparalleled freedom of movement.
- The columns may even be moved outside for use on a level concrete surface with a minimum thickness of six (6) inches.
- The mobile columns can be easily stored out of the way when not in use.
- Advanced system with automatic lifting/lowering speed variety ensures synchronization of all columns during lifting/lowering phase.
- Operation can be controlled from every column's touch screen control panel.
- Touch screen with instructions for user friendly operation
- Adjustable forks to accommodate different tyre diameters.
- Safety stop in case of malfunction.
- Double-safety guaranteed by both hydraulic flow control and mechanical locks

- Can be operated from any column
- Battery Charger system in each column
- Internal Batteries (24V) operating system
- LCD screen display
- Automatic stop when highest point is reached
- Fully synchronised lift & lowering cycles with full mechanical safety locks
- Adjustable wheel tines for small to large diameter wheels





Each column has a Touchscreen control panel with, buttons for UP - DOWN - LOCK - TURTLE DOWN. Full control from every column



- Adjustable forks for different wheel diameters, guaranteeing suitability across all vehicle categories including agricultural



Each heavy duty mobile column is powered by a DC motor equipped with a set of DC rechargeable batteries & batter charger.

SPECIFICATIONS

| | |
|---------------------------------------|-------------|
| load capacity per column | 8500kg |
| Lifting stroke | 1700mm |
| Width between adjustable forks | 240mm-624mm |
| Lifting time (approx) | 120sec |
| Weight per column | 810kg |
| Power supply (battery charger) | 230V 1PH |
| Max height difference between columns | 50mm |
| Motor power | 2.2kw DC24V |

AUTOMASTER AM-7607D Motorcycle Lifter




SCAN ME

- This high quality commercial grade motorcycle lift is the ideal solution for motorcycle servicing and repairs.
- Its has optional side platforms that can be added to turn this versatile lift into a quad bike or mini tractor lift.
- Retractable drive up ramp
- Removable rear platform section
- Wheel vice included
- Ramp included
- Tool tray included
- Full hydraulic operation
- Safety locks at any height



| SPECIFICATIONS | |
|----------------|----------|
| Capacity | 700kg |
| Length | 2220mm |
| Width | 730mm |
| Max height | 1200mm |
| Min height | 160mm |
| Weight | 200 kg |
| Power | 230V 1Ph |
| Warranty | 1 year |

Change the width with an optional ATV side kit



AUTOMASTER AM-7530 Mid-Rise Scissor Lift



SCAN ME

- The perfect lift for wheel & tyre, brake and suspension service specialists.
- Free standing portable Mid Rise scissor lift
- Pneumatic mechanical safety locking system
- Electro-hydraulic lifting system
- Lock up ramps to extend length
- 4 x 40mm + 4 x 80mm rubber lifting blocks included
- Portable wheel kit included
- 10 Amp NZ Single phase plug
- Air regulator/moisture trap & oiler, and oil hose covers included
- Optional 4x4 kit & Optional low car ramp kit





Shown with optional low car ramp extension kit

| SPECIFICATIONS | |
|-----------------------|--------|
| Capacity | 3000kg |
| Max height | 1000mm |
| Min height | 100mm |
| Lifting time (approx) | 35sec |
| Weight | 600kg |
| Power supply | 220V |
| Warranty | 2 Year |



Red or Blue normally in stock



AUTOMASTER AM-7130DH Ultra Low Profile Scissor Lifter




- Full rise scissor lift combines an extremely low lift platform height of 100mm and an impressive 1900mm full height position
- Powered by four powerful hydraulic cylinders.
- Extendable foldable ramps at both ends of the main platforms permit the lifting of long vehicle with ease.
- Above ground, or flush mounted lift
- Lock up ramps to extend length
- 10 position air actuated lock system is automatically engaged and disengaged as the lift is being raised or lowered.
- 4 x 40mm + 4 x 80mm rubber lifting blocks included
- Air regulator/moisture trap & oiler, and oil hose covers included
- 10 Amp NZ Single phase plug
- Optional 4x4 kit & Optional low car ramp kit



| SPECIFICATIONS | |
|-----------------------|--------------------------|
| Capacity | 3000kg |
| Lifting height | 1900mm |
| Min height | 100mm |
| Motor power | 2.2kw |
| Weight | 960kg |
| Lifting time (approx) | 50-60sec |
| External dimensions | 1900(L) 2050(W) 115(H)mm |



OPTIONAL LOW CAR RAMP KIT



Optional Van Lifting kit

POWERREX SL-34DX
Full Rise Scissor Lifter



SCAN ME


MADE IN SOUTH KOREA




- Premium quality, feature rich, genuine 100% Korean manufactured
- Only two metres wide, this hoist can be installed anywhere a vehicle will fit.
- With a 2 Metre lift height, this hoist also ensures comfortable under body repair for any technician
- 3.3 tonne lift capacity
- Extendable platform length
- Excellent under vehicle access
- Twin ram construction



| SPECIFICATIONS | |
|---------------------|-------------------------|
| Lifting capacity | 3300kg |
| Lifting height | 2045mm |
| Lifting time approx | 45-55 sec |
| External dimensions | 3680mm (L) - 1975mm (W) |
| Motor power | 1 or 3ph |



IN-GROUND INSTALL



ON-GROUND INSTALL

PEAK P-407//P-408P// P-409HP Parking Lifts

Home Workshop Series



- Featuring PEAK's exclusive hidden safety locks, adjustable locking ladders for perfect leveling and manual single-point lock release device
- 4 x drip trays come as standard
- Ramps easily removed for storage
- Jack tray included
- Double S shape columns
- European CE Safety Certified

SPECIFICATIONS 407P/408P/409HP







| | |
|-------------------|------------------|
| Capacity | 3000/3500/4000kg |
| Length incl ramps | 4720/5257/5857mm |
| Width | 2409/2784/3206mm |
| Max Height | 1872/1872/2172mm |
| Min Height | 135/155mm/155 |
| Weight | 654/832/990kg |
| Warranty | 2 Years |
| Power supply | 230V 1PH 15amp |

THE CONCRETE MUST:

- Have a minimum thickness of 100mm
- Be reinforced
- Be a grade of no less than 25MPA



IMAGE SHOWING OPTIONAL JACKING BEAM



WHY NOT UPGRADE WITH AN OPTIONAL JACKING BEAM OR CASTER KIT



MULTI POST CONTROL UNIT POSITIONING




ADJUSTABLE LOCK LADDERS



UNIQUE 'S' BEND POST DESIGN



LOCK RELEASE LEVER



4 X DRIP TRAYS AND JACK TRAY INCLUDED

AUTOMASTER AM-6745L

Four Post Hoist

- A low minimum height of 130mm & 970mm long drive on ramps means the lift can handle low riding cars as well as light commercial vehicles
- Mechanical locking system
- Double lock safety system is automatically activated as the lift is raised & includes a cable breakage emergency locking system should there be a failure.
- Wide and long to accommodate large vehicles
- Total length 5920mm
- Optional jacking beams
- European CE Safety Certified






SCAN ME



OPTIONAL ROLLING JACKING BEAMS

| SPECIFICATIONS | |
|-----------------------|------------------|
| Capacity | 4200kg |
| Lift height | 1800mm |
| Min height | 130mm |
| Lifting time (approx) | 50sec |
| Weight | 1500 |
| Power supply | 230V or 380v/3ph |
| Warranty | 2 Year |

The adjustable locking ladders in each post enable simple levelling of the lift and ensure all 4 corners of the lift are locked.



THE CONCRETE MUST:

- Have a minimum thickness of 150mm
- Be reinforced
- Be a grade of no less than 25MPA

AUTOMASTER AM-6745WA Wheel Alignment Hoist

- Multi position turn table recesses and multi-directional lockable rear slip plates
- Automatically engaging locking system
- Cable breakage emergency locking system
- Pneumatically operated unlocking system is operated by simply pushing a button on the control panel.
- 2 x 2500Kg rolling jacking beams included to give a wheels free operation for when you need to replace all four tyres or carry out a tyre rotation
- Adjustable locking ladders in each post enable perfect leveling of the lift
- European CE Safety Certified






2 X ROLLING JACKING BEAMS - INCLUDED AS STANDARD

| SPECIFICATIONS | |
|-----------------------|------------------|
| Capacity | 4200kg |
| Lift height | 1850mm |
| Min height | 180mm |
| Lifting time (approx) | 50sec |
| Weight | 1500 |
| Power supply | 230V or 380v/3ph |
| Warranty | 2 Year |



THE CONCRETE MUST:

- Have a minimum thickness of 150mm
- Be reinforced
- Be a grade of no less than 25MPA



AUTOMASTER AM-6764-L
6400kg Four Post Hoist




- Optional bolt on alignment package
- Automatically engaging locking system
- Cable breakage emergency locking system
- Pneumatically operated unlocking system is operated by simply pushing a button on the control panel.
- Wide and long to accommodate large vehicles
- Total length 7080mm
- Runway width 512
- Optional 3200kg jacking beams
- European CE Safety Certified




| SPECIFICATIONS | |
|-----------------------|----------|
| Capacity | 6400kg |
| Lift height | 1850mm |
| Min height | 180mm |
| Lifting time (approx) | 70sec |
| Weight | 1800 |
| Power supply | 380v/3ph |
| Warranty | 2 Year |

Optional Bolt on Alignment Kit




OPTIONAL ROLLING JACKING BEAMS




THE CONCRETE MUST:

- Have a minimum thickness of 150mm
- Be reinforced
- Be a grade of no less than 25MPA



Optional Bolt on Alignment Kit



AUTOMASTER AM-8250TXD-R Alignment Scissor Lift



- Maximum capacity of 5000kg
- Suitable for 4x4's, vans, low cars, American cars, utes etc.
- 2 x rolling centre jacking beams controlled by buttons on each jack
- Remote controlled operation
- Full floating rear slip plates
- Wide and long to cover large and small vehicles
- Can be used with standard CCD or 3D alignment systems
- Total length 5826mm
- Normally available in red or blue
- Space saving design
- Can be surface or flush mounted
- European CE Safety Certified






| SPECIFICATIONS | |
|----------------|----------|
| Capacity | 5000kg |
| Max height | 2160mm |
| Min height | 290mm |
| Lifting time | 45sec |
| Runway length | 5000mm |
| Power supply | 380v/3ph |
| Warranty | 2 years |



Rear Support Bar

Turntables can be placed in three different positions



Air actuated main locks

THE CONCRETE MUST:

- Have a minimum thickness of 150mm
- Be reinforced
- Be a grade of no less than 25MPA

POWERREX KOREA SL-3600A & SL-3600L Four Post Hoist



MADE IN SOUTH KOREA



- **SL3600A Alignment Lift**
- **SL3600L Standard Lift**
- Manufactured in Korea
- Premium quality four post lift supplied with two centre jacking beams as standard
- Featuring a 3 button control panel for up, lock and down and a 6 button remote control with up and down control for the lift and each jacking beam.
- Each jacking beam also has electrical switches on each side to operate them
- Jacking beams are powered by the main hydraulic pump of the lift there is no need to run pneumatic air lines to the jacks.
- Automatic electrical safety lock system
- Cable breakage emergency locking system
- Wide and long to accommodate large vehicles
- Australia/NZ safety certified

SL3600A wheel alignment hoist includes multi position turntable recesses and rear slip plates for wheel alignment. Jacking beams are also included.






RED OR BLUE
NORMALLY AVAILABLE



| SPECIFICATIONS | |
|---------------------------|------------------|
| Capacity | 4500kg |
| Lift height | 1750mm |
| Min height | 235mm |
| Lifting time (approx) 3PH | 40-50sec |
| Weight | 1800 |
| Power supply | 230V or 380v/3ph |
| Warranty | 2 Year |



| MODEL NO. | SL-3600A (JACK TYPE) |
|--------------------|---|
| MAX.CAPACITY | MAIN 4,500 Kg JACK 2,000 Kg |
| MAX.LIFTING HEIGHT | MAIN 1,750 mm JACK 540 mm |
| LOWEST HEIGHT | MAIN 235 mm JACK 205 mm |
| SIZE (mm) | 3,350W x 2,165H x 6,060L |
| LIFTING TIME | MAIN 50 sec.(Approx) JACK 35 ~ 45 sec.(Approx) |
| LOWERING TIME | MAIN 60 ~ 80 sec.(Approx) JACK 65 ~ 80 sec.(Approx) |
| POWER & MOTOR | Single 2.5HPx3Px220Vx50/60Hz 3phase 2HPx5Px380V/415Vx50/60Hz |
| OPERATION METHOD | Control panel / Wired remote control type |



POWERREX KOREA SL6000A & SL6000L Four Post Hoist



- **SL6000A Alignment Lift**
- **SL6000 Standard Lift**
- Manufactured in Korea
- A 6000kg premium quality four post wheel alignment lift supplied with two centre jacking beams as standard to give a wheels free operation for when you need to replace all four tyres or carry out a tyre rotation.
- Featuring a 3 button control panel for up, lock and down and a 6 button remote control with up and down control for the lift and each jacking beam.
- Each jacking beam also has electrical switches on each side to operate them while in place under the car.
- As the jacking beams are powered by the main hydraulic pump of the lift there is no need to run pneumatic air lines to the jacking beams
- Automatic electric safety lock system
- Cable breakage emergency locking system
- Australia/NZ safety certified






| SPECIFICATIONS | |
|---------------------------|----------|
| Capacity | 6000kg |
| Lift height | 1785mm |
| Min height | 280mm |
| Lifting time (approx) 3PH | 50-60sec |
| Weight | 1800 |
| Power supply | 380v/3ph |
| Warranty | 2 Year |

| MODEL NO. | SL-6000A (JACK TYPE) |
|--------------------|--|
| MAX.CAPACITY | MAIN 6,000 Kg JACK 3,000 Kg |
| MAX.LIFTING HEIGHT | MAIN 1,785 mm JACK 580 mm |
| LOWEST HEIGHT | MAIN 280 mm JACK 245 mm |
| SIZE (mm) | 3,618W x 2,165H x 7,538L |
| LIFTING TIME | MAIN 75 ~ 85 sec. (Approx) JACK 35 ~ 45 sec. (Approx) |
| LOWERING TIME | MAIN 60 ~ 65 sec. (Approx) JACK 65 ~ 80 sec. (Approx) |
| POWER & MOTOR | 3phase 3HPx5Pcx380V/415Vx50/60Hz |

THE CONCRETE MUST:

- Have a minimum thickness of 150mm
- Be reinforced
- Be a grade of no less than 25MPA



POWERREX KOREA
SL8000/SL10000
Four Post Vehicle Hoist



- SL8000 8000kg lift
- SL10000L10000kg lift
- Manufactured in Korea
- Supplied with 2 x jacking beams
- Automatic safety lock system
- Cable breakage emergency locking system
- Wide and long to accommodate large vehicles
- Total length 7820mm/8910mm
- Runway width 700
- Meets Australia/NZ safety regulations and
- European CE safety certified





| SPECIFICATIONS | |
|---------------------|------------------|
| | SL8000 / SL10000 |
| Capacity | 8000kg / 10000kg |
| Lift height | 1750mm |
| Min height | 280mm / 260mm |
| Lifting time approx | 45-55 sec |
| Weight | 1800kg |
| Power supply | 380v/3ph |
| Warranty | 2 years |



SPECIAL ORDER ONLY

THE CONCRETE MUST:

- Have a minimum thickness of 200mm
- Be reinforced
- Be a grade of no less than 25MPA



SL10000



POWERREX SL-5600A

4.5 Tonne Wheel Alignment Scissor





SCAN ME



- Premium quality Korean made
- 2 x centre jacking beams are also included permitting the operator to lift the wheels free of the platforms
- 3 button control panel for up, lock and down and a 6 button remote control with up and down control for the lift and each jacking beam.
- Each jacking beam also has electrical switches on each side to operate them while in place under the car.
- As the jacking beams are powered by the main hydraulic pump of the lift there is no need to run pneumatic air lines to the jacking beams.
- Space saving design
- Automatic locking system

| SPECIFICATIONS | |
|---------------------|---------------|
| Lifting capacity | 4500kg |
| Lifting height | 1850mm |
| Lifting time approx | 45-55 sec |
| External dimensions | 2150W x 6090L |
| Motor power | 3ph |



COLOUR
OPTIONS:
RED OR
BLUE



POWERREX SL-6600A
6.0 Tonne Wheel Alignment
Scissor





SCAN ME

MADE IN SOUTH KOREA



- Premium quality Korean made
- 2 x centre jacking beams are also included permitting the operator to lift the wheels free of the platforms
- 3 button control panel for up, lock and down and a 6 button remote control with up and down control for the lift and each jacking beam.
- Each jacking beam also has electrical switches on each side to operate them while in place under the car.
- As the jacking beams are powered by the main hydraulic pump of the lift there is no need to run pneumatic air lines to the jacking beams.
- Space saving design
- Automatic locking system



| SPECIFICATIONS | |
|---------------------|---------------|
| Lifting capacity | 6000kg |
| Lifting height | 1900mm |
| Lifting time approx | 55 sec |
| External dimensions | 2250W x 7660L |
| Motor power | 3ph 380V |



CORGI EXACT 7 - 8CCD Wheel Aligner



- 0.01° data display
- Wireless Data transfer
- 10" to 26" Ultra light Carbon Clamps- ROC Skip Clamps
- Intuitive two key operation
- User friendly software with easy access tutor help
- Easy access to all adjustment values
- Re-chargeable AA batteries
- Graphic indications for adjustment
- Chassis measurement data
- Total toe ± 20°Half toe ± 10°Camber ± 10°Caster ± 30°King-pin ± 30°Set back ± 10°
- A first class world based databank
- User databank insert for modified vehicle data
- Customer data bank, to recall and memorize all customer data.
- Short measurement cycles, quick alignment results



Computerised wireless wheel alignment centre from Corghi with a highly competitive price. EXACT 7 is a professional wheel aligner with 8 sensors for passenger cars and vans. **Measuring sensor** with 2 high resolution cameras, electronic inclinometer and level. Wireless data transmission with 2.4 GHz industrial radio systems. Commercially available AA rechargeable batteries with recharger on unit. Extremely compact and light (just 3.2 Kg). Extremely low light sensitivity for working even in very bright light conditions. Measuring sensor body in cast aluminum for extreme precision!

ACCESSORIES SUPPLIED

- 10" to 26" Ultra light Carbon Clamps- ROC Skip Clamps
- Colour 24"LCD Monitor
- Colour printer
- Pair of 50mm turntables
- Brake pedal depressor
- Steering wheel holder
- Corghi EXACT alignment software



ASK US ABOUT HOIST AND WHEEL ALIGNER PACKAGES




**CORGI EXACT LINEAR PLUS
3D Wheel Aligner - BASIC KIT**



SCAN ME

- Based on WIN 10 software
- New 10 Megapixel high-resolution cameras for HI-Q artificial vision with anti-reflection nano coating.
- Enhanced protection against light interference thanks to measurement by image difference.
- Integrated LPF filter to eliminate sunlight reflections.
- New compact high-resolution light targets
- New cabinet with integrated targets and clamp holders
- New Camera Movement with worm-gear
- User friendly software with tutor & graphic indications which guides the operator step by step
- Fast and simple vehicle selection from database
- Factory calibrated, calibration check on installation then no need for regular calibration.
- A first class world based data-bank with upgrade kit for North American market vehicles included
- User data-bank insert for modified vehicle data




**HIGH-RESOLUTION
LIGHT TARGET**
Front infrared filter for enhanced immunity to solar reflections.



HIGH QUALITY CAMERA
High resolution HI-Q latest generation camera

Optimized monolithic optics with low distortion .
Nano anti-reflection coating & Integrated LPF filter to eliminate sunlight reflections.
Light operational indicators of caster swing and run out.

| ACCESSORIES SUPPLIED |
|--|
| Set of Standard 11" to 21" clamps |
| Adaptor for clamps up to 25" wheels |
| Motorised camera boom movment |
| Pair of standard 50mm high turntables |
| Turntable adaptors for push mode ROC procedure |
| Steering wheel holder & Brake pedal depressor |
| USA Data bank upgrade included |
| PC with 24" LCD monitor & Colour printer |



CORGI EXACT LINEAR PLUS 3D Wheel Aligner - PREMIUM KIT




- Based on WIN 10 software
- New 10 Megapixel high-resolution cameras for HI-Q artificial vision with anti-reflection nano coating.
- Enhanced protection against light interference thanks to measurement by image difference.
- Integrated LPF filter to eliminate sunlight reflections.
- New compact high-resolution light targets
- New cabinet with integrated targets and clamp holders
- New Camera Movement with worm-gear
- User friendly software with tutor & graphic indications which guides the operator step by step
- Fast and simple vehicle selection from database
- Factory calibrated, calibration check on installation then no need for regular calibration.
- A first class world based data-bank with upgrade kit for North American market vehicles included
- User data-bank insert for modified vehicle data

PREMIUM KIT INCLUDES

- 10" to 26" Ultra light Carbon Clamps- Made in Italy
- Auto tracking of target and lift level for camera boom movement
- Nexremote tablet included
- 27"LCD monitor



| ACCESSORIES SUPPLIED |
|--|
| Set of 10" to 26" Ultra light Carbon Clamps - Made in Italy |
| Auto target tracking for camera boom movement |
| Nexremote tablet included |
| Pair of turntables |
| Turntable adaptors for push mode ROC procedure |
| PC with 27"LCD monitor & Colour printer |
| Brake pedal depressor & Steering wheel holder |
| Motorised worm drive camera boom movement |
| USA Data bank upgrade included |



Camera movement kit allows **AUTOMATIC TRACKING OF LIFT LEVEL.**




HIGH-RESOLUTION LIGHT TARGET
With infrared filter for enhanced immunity to solar reflections.

Includes Nexremote tablet. This tablet is used as a remote control of the graphical user interface or as an additional screen.



HIGH QUALITY CAMERA
High resolution HI-Q latest generation camera

Optimized monolithic optics with low distortion .
Nano anti-reflection coating & Integrated LPF filter to eliminate sunlight reflections.
Light operational indicators of caster swing and run out.





Corghi & Automaster Wheel Lifters

Automaster PFL-65 Wheel Lifter

- Back saving wheel lifter for passenger car, light transport vehicle and motorcycle wheels.
- Lifts & lowers wheels for mounting on the wheel balancer
- Toggle switch control



| SPECIFICATIONS | |
|------------------|--------------|
| Lifting Capacity | 65kg |
| Max lift height | 486mm |
| Min height | 162mm |
| Air Pressure | 100 -145 psi |
| Overall height | 809mm |

Automaster YCW-200 Wheel Lifter

- Portable pneumatic wheel lifter
- Move wheels from vehicle to balancer or tyre changer
- Toggle switch control



| SPECIFICATIONS | |
|-----------------------|--------------|
| Lifting Capacity | 80kg |
| Max lift height | 1030mm |
| Min height | 130mm |
| Air Pressure | 100 -145 psi |
| Overall height | 1470mm |
| Arm length | 450-700mm |
| Distance between arms | 190-500mm |

Corghi TT-R Wheel Lifter

- Adjustable scissor wheel lifter for passenger car, SUV and light transport vehicle.
- For lifting and centring wheels weighing up to 80 kg, without the need for any physical effort.
- Simple: the wheel height is adjusted by simply rotating the handle.
- Ergonomic: the controls and accessory mounts are designed to be in the ideal position for use.
- Safe: eliminates any risk of accidents caused by the lifting of heavy loads
- Rim protection: a polyurethane guard on the side of the trolley protects the rim from damage during the wheel loading and unloading phases



| SPECIFICATIONS | |
|------------------|--------------|
| Lifting Capacity | 80kg |
| Max lift height | 565mm |
| Min height | 105mm |
| Max wheel width | 19" |
| Air Pressure | 100 -145 psi |

Corghi TT-0 Zero Gravity Wheel Lifter

- Automatic self-balancing wheel lifter for passenger car, light transport vehicle and motorcycle wheels
- Self-balancing: the lifter features a special pneumatic system which completely eliminates the weight of the wheel, for effortlessly lifting and centring wheels weighing up to 80 Kg.
- Automatic: wheels are unloaded from wheel balancer completely automatically with no manual adjustment required from the operator.
- Fast: much faster operation than a conventional manually controlled lifter
- Ergonomic: the controls and accessory mounts are designed to be in the ideal position for use
- Optimised centring: the special self-balancing system ensures that the wheel is centred more precisely, eliminating clamping misalignment caused by the weight of the wheel



| SPECIFICATIONS | |
|------------------|--------------|
| Lifting Capacity | 80kg |
| Max lift height | 565mm |
| Min height | 105mm |
| Max wheel width | 19" |
| Air Pressure | 100 -145 psi |

Corghi Partner 70 wheel Lifter

- Battery-operated wheel lifter
- Partner 70 helps you to easily and safely demount, move and mount the wheels of cars, SUVs and light transport vehicles weighing up to 70kg.
- Move wheels from the lift to the tyre machine and the balancer easily and safely
- It's the only lifter without support forks protruding forward on the ground.
- Thanks to this feature, it can be used with any type of lift, even those with a base and with parts fixed to the ground.




| SPECIFICATIONS | |
|-------------------------|--------|
| Lifting Capacity | 70kg |
| Max lift height | 1220mm |
| Floor- wheel center 24" | 1650mm |
| Battery | 24V |
| Lift weight | 198kg |


AUTOMASTER AM-7515 Electric vehicle battery lift table



- Supplied only in dark grey RAL-7016
- 1500Kg Capacity
- Mobile unit
- 240v Powerful Hydraulic unit
- Operational Height 740mm – 1800mm
- Table dimensions 1728 – 2027mm x 810mm
- Fully adjustable and lockable table for precise alignment
- Optional Subframe adapter kit
- Easy to operate and manoeuvre
- Pallet truck style pump unit
- Fully adjustable screw jacks to level and tilt the lift table
- The lift bed is mounted on lockable ball bearings for easy X and Y adjustment when loaded
- M8 threaded holes spaced every 50mm
- Lockable, extendable lift table mounted on metal rollers
- Powerful 240v hydraulic unit with remote controls




The optional seventy piece subframe adjustable adapter kit comprises of precisely manufactured components to convert the AS-7515 EV lift table into a safe and secure lifting platform for removing drive train subframe assemblies



Optional subframe adjustable adapter kit

M8 threaded holes spaced every 50mm





PATCH RUBBER
TYRE AND TUBE
EVERYTHING FOR THE TYRE DEALER



SCAN ME

AUCKLAND: 0508 837 248
HAMILTON: 0508 489 737
WELLINGTON: 0800 943 777
CHRISTCHURCH: 0800 936 444
INVERCARGILL: 0508 472 824

Tyre Repair Materials & Tools



Inflation Tools & Gauges



Wheel Balancing Supplies



Air Tools, Hose & Fittings



Valves, Extensions & TPMS



Tyre Changing, Levers & Hammers





PATCH RUBBER
TYRE AND TUBE
EVERYTHING FOR THE TYRE DEALER



SCAN ME

AUCKLAND: 0508 837 248
HAMILTON: 0508 489 737
WELLINGTON: 0800 943 777
CHRISTCHURCH: 0800 936 444
INVERCARGILL: 0508 472 824

Specialty Tyres for ATV, Agricultural Machines, Skidsteer, Forklift, Industrial, Lawn, Garden, Golf, Motorcycle and Trailer uses.



NZ's Largest Range of Inner Tubes



Tyre Mount/Demount Lubricants



Scan this QR code to complete an account application form .

Patch Rubber Tyre & Tube is a wholesale distributor to our industry and as such we do not sell our products direct to any purchaser who does not hold an approved trade related credit account



SCAN ME

Bead Breaking & Bead Seaters



/// AUTO MASTER

0800 214 604

info@automaster.co.nz

87 Henderson Valley Road, Henderson,
Auckland

SALES - 0800 214 604

info@automaster.co.nz

John Milne

021 784 620 / john@automaster.co.nz

Jeremy Gilbert

021 2784 604 / jeremy@automaster.co.nz

Bryan Atkins - South Island

022 361 8064 / bryan@automaster.co.nz

AFTERSALES SUPPORT - 0800 214 604

Gary Bartlett

021 2784 233 / service@automaster.co.nz

JK - John Karathanasis

027 535 5126 / jk@automaster.co.nz

AFTERSALES & PARTS - 0800 214 604

Brad Miller

022 024 1106 / brad@automaster.co.nz

www.automaster.co.nz

