

WL60



General description

The WL 60 wheel lift is designed for customers who work with **large, heavy wheels on an everyday basis**. Installed in front of the tyre changer, it integrates with the basic machine to perfection, **eliminating all vertical wheel lifting effort**. It complies with **all workplace safety regulations**. What's more, the WL 60's roller bed lift platform makes bead breaking quicker and easier.

Main characteristics

- **Wheel lift** ideal for large tyres (balloon and light truck)
- Fully pneumatic operation
- For installation on the front of the tyre changer



➤ Easier wheel positioning on the turntable

Technical data

lifting capacity	60 kg
operation	pneumatic
operating pressure	8-10 bar
lift weight	20 kg

Technical data

A2030 A2025 A2020

turntable	internal clamping capacity	from 13" to 26"	from 13" to 26"	from 13" to 26"
	external clamping capacity	from 10" to 26"	from 10" to 24"	from 10" to 20"
	maximum tyre diameter	1100 mm / 43"	1100 mm / 43"	1100 mm / 43"
maximum tyre width 360 mm / 14"	360 mm / 14"	360 mm / 14"	360 mm / 14"	
	n. of clamps	4	4	4
	n. of cylinders	2	2	2
rotation torque	-	1200 Nm	1200 Nm	1200 Nm
DV version rotation torque	1300 Nm	1300 Nm	1300 Nm	1300 Nm
rotation speed	-	8 rpm	8 rpm	8 rpm
DV version rotation speed	from 6 to 15 rpm	from 6 to 15 rpm	from 6 to 15 rpm	from 6 to 15 rpm
height above the ground	675 mm	675 mm	675 mm	665 mm
bead breaker	type	adjustable arm with extending shoe	fixed arm with extending shoe	fixed arm
	maximum opening	380 mm	380 mm	380 mm
shoe force	15500 N	15500 N	15500 N	15500 N
support	telescopic	telescopic	telescopic	telescopic
tool	working range	from 8" to 26"	from 8" to 26"	from 8" to 24"
	column	pneumatic tilting	pneumatic tilting	pneumatic tilting
power supply	head clamping	pneumatic	pneumatic	pneumatic
	electrical 3ph	-	230/400 V - 0.75 kW	230/400 V - 0.75 kW
electrical 1ph	-	110/230 V - 0.75 kW	110/230 V - 0.75 kW	110/230 V - 0.75 kW
DV version electrical 1ph	230 V -0.75 kW	230 V - 0.75 kW	230 V - 0.75 kW	230 V - 0.75 kW
pneumatic	-	on request	on request	on request
operating pressure	10 bar	10 bar	10 bar	10 bar
weight	standard version	249 kg	249 kg	242 kg
	T.I. version	259 kg	259 kg	252 kg



A2030
A2030
A2030
A2030
A2030
A2030

A2025
A2025
A2025
A2025
A2025
A2025

A2020
A2020
A2020
A2020
A2020
A2020

A2030
A2030
A2030
A2030
A2030
A2030

A2025
A2025
A2025
A2025
A2025
A2025

A2030
A2030
A2030
A2030
A2030
A2030

A2020
A2020
A2020
A2020
A2020
A2020

A2025
A2025
A2025
A2025
A2025
A2025

A2030
A2030
A2030
A2030
A2030
A2030

A2020
A2020
A2020
A2020
A2020
A2020

A2025
A2025
A2025
A2025
A2025
A2025

