



AUTOMASTER

THE AUTO EQUIPMENT SPECIALISTS

Automaster AM-838

Platinum Series Wheel Balancer

PLATINUM



Automaster AM-838

Platinum Series Wheel Balancer



OUR VICE-GRIP GUARANTEE

If you're not happy, we replace or refund in full.



Real-time 19" HD Color TFT Monitor display with
3D wheel animation live graphics



Optional : Double sided cone & spacer centring
accessory for van light truck and
off-road wheels
Ø 118-140mm & 147-160mm

Automatic measuring of wheel width by sonar for
contactless measurement of wheel width



FEATURES

- Real-time TFT Monitor display with 3D wheel animation
- Handles rims up to 30" diameter
- Automatic input of wheel diameter and distance by arm
- Automatic measuring of wheel width by touchless SONAR
- Laser guidance for precise weight placement
- LED illumination inside rim for clear visibility
- Electromagnetic autolocking brake for ease of weight application
- Fast & Easy Split (FES) function allows for behind the spokes positioning of weights
- Special Alu-S Programs. Programs for selecting the best correction planes for any kind and shape of alloy rim
- Opposite Weight Function (OWF) allows for 6 o'clock application of balance weights
- "No Wheel Needed" (NWN) system for calibrating gauges, without need for any sample wheel.
- Automatic stop/start via lifting of wheel guard
- Three modes for adhesive weights: distance arm clip, with the 6 o'clock laser or manually at 12 o'clock.
- Opti-match function for best position of the tyre on the rim. (optimization of the unbalance between rim and tyre).
- Simple self calibration function
- European CE Safety Certified
- Full 2 year warranty
- **Components Made in Italy**, Haweka quick nut (Germany) Electronic boards, Picks ups, Rotation sensors, Width sonar, Motor belt, Electric cables and connectors

The adhesive weights can be positioned easily and rapidly using the laser guidance for precise weight placement at 6 o'clock position.

The integrated LED illumination inside rim for clear visibility of the work area



Automaster AM-838

Platinum Series Wheel Balancer



OUR VICE-GRIP GUARANTEE

If you're not happy, we replace or refund in full.



Cone set with Haweka quick nut from Germany



SPECIFICATIONS

Spinning speed	<150 rpm
Measurement accuracy	1g
Average spin time	5-6s
Rim width	1.5-20"
Rim diameter	10-30"

SPECIFICATIONS

Power supply voltage	230V 1Phase
Maximum wheel weight	75KG
Shaft diameter	40mm
Machine weight	120kg
Maximum wheel diameter	1100mm (with hood)

